### Hisense

# CEIL COOL 360° ROUND AIRFLOW

Professional quality Comfortable space













236mm Ultra-thin Body Slim And Saves More Space



Multiple Control Methods Choose As You Like

#### Various Styles, Suitable For Various Places







#### ALL-ROUND HEALTH SUPPLY YOU HIGH QUALITY AIR







**Easy-to-clean Filter**Effectively filter harmful particles

#### ALL-ROUND COMFORT ENJOY LIFE TO YOUR HEART'S COMTENT



#### 360° Round Flow

Uniform temperature distribution



#### **Ideal Wind**

Reaches every corner and enjoy natural cool breeze



#### **Big Louver**

With 88° free swinging angle



#### Brand new silent air duct design

Silent air supply with optimized blades and professional duct simulation, create a peaceful environment.

#### ALL-ROUND QUALITY ASSURANCE EFFICIENT, SAFE AND RELIABLE



#### R32 Refrigerant

Environmentally friendly and efficient

4-Positions of

Suspension Bolts

840

Optional Panel

Drain Piping Connection Side

(Unit Size) 860 to 910 ension of Open

**Backward Centrifugal Fan** 

With excellent air supply, high

efficiency, low noise and loss,

higher reliability.

Piping Connection side



#### Flexible Installation

Anti-overflow design and high-lift water pump, pipeline installation is more flexible




#### **Five-fold Evaporator**

No backflow, smooth drainage 1.2M

Larger heat exchange area, higher efficient, more power-saving than traditional four-fold evaporator.

#### **Installation Dimensions**



#### **Mounting Position Of Indoor Unit**

\*Indicates the dimension between lower face of indoor unit and surface of ceiling.

(4-Suspension Bolts)
M10 or W3/8 (Field-Supplied)

W-Nut (Field Supplied)
Washer (Accessary)

Washer (Accessary)

#### Ceiling Cassette Air Conditioner Specification ≡

MODEL			AUC20QFGS	AUC25QFGS	AUC35QFGS	AUC40QFGS	AUC45QFGS	AUC50QFGS
Indoor model			AUC-18CR4RJA	AUC-24CR4RJA	AUC-30CR4RKA	AUC-36CR4RKA	AUC-42CR4RKA	AUC-48CR4RKA1
Outdoor model			AUW-18C4RM	AUW-24C4RB	AUW-30C4RB	AUW-36C4RD	AUW-42C6RE	AUW-48C6RE1
Power supply V-ph-		V-ph-Hz	220~240-1-50	220~240-1-50	220~240-1-50	220~240-1-50	380~415-3-50	380~415-3-50
Power factor		0.98	0.98	0.97	0.98	0.90	0.9	
Rated consumption		W	1700	2215	2582	3245	3600	4280
Rated current		Α	7.5	9.8	11.5	14.7	6.8	7.8
Cooling	Capacity T1	Btu/h	19670	26000	32800	37425	44880	49500
Indoor air flow rated (Hi/Med/Lo)		m3/h	1300/1200/1050	1300/1200/1050	2000/1850/1550	2000/1850/1550	2000/1850/1550	2000/1850/1550
Indoor noise level (Hi/Med/Lo)		dB(A)	45/42/40	45/42/40	55/53/50	55/53/50	55/53/50	55/53/50
Indoor unit	Dimension (W×H×D)	mm	840×236×840	840×236×840	840×272×840	840×272×840	840×272×840	840×272×840
	Packing(L×W×H)	mm	950x950x320	950x950x320	950×950×360	950×950×360	950×950×360	950×950×360
	Net/Gross weight	kg	23.5/29.0	23.5/29.0	28.0/34.5	28.0/34.5	28.0/34.5	28.0/34.5
Operation temperature °C		°C	16~46	16~46	16~46	16~46	16~46	16~46
Outdoor noise level (sound pressure)		dB(A)	53	56	56	58	56	56
Outdoor unit	Dimension(W×D×H)	mm	780×260×540	860×310×665	860×310×665	885×366×795	950×340×1050	950×340×1050
	Packing(L×W×H)	mm	910×600x360	995×720×420	995×720×420	1050×500×890	1110×460×1200	1110×460×1200
	Net/Gross weight	kg	34/36	46/49	54/57	65/70	77/88	80/91



With the products exported to over 160 countries and regions, Hisense has also sponsored the world's top sporting events such as UEFA EURO 2016, 2018 FIFA World Cup, UEFA EURO 2020 and FIFA World Cup 2022<sup>TM</sup>. Hisense Group has 29 industrial parks and production bases, which are located in Qingdao, Shunde, Jiangmen, Yangzhou, Guiyang, Huzhou, Czech Republic, South Africa, Mexico and so on. There are also 20 R&D centers located in Qingdao, Shanghai, Shenzhen, USA, Europe, Israel, Japan, etc.



## Penang Sabah Ipoh Kuala Lumpur (HQ) East Coast Sarawak

**Hisense Malaysia Branches** 

#### HISENSE (MALAYSIA) SDN. BHD

Level 1, Oasis Wing, Brunsfield Oasis Tower 3, Oasis Square, No. 2, Jalan PJU 1A/7A, Oasis Damansara, 47301, Petaling Jaya, Selangor.

T: 603 7859 9550 www.hisense.com.my